









微調精磨刀

MICRO-ADJUSTABLE FINE BORING TOOL



規格 SPECIFICATION	搪孔徑 BORING DIA. ϕD	微調單元 MICRO-ADJUSTING UNIT	調整範圍 ADJUSTING RANGE	柄徑 ϕd	刃長 J	全長 L
S20C-MBU18-45	$\phi 18$	MBU18	$\phi 17.7 \sim \phi 20.0$	$\phi 20$	45	95
S20C-MBU20-50	$\phi 20$	MBU20	$\phi 19.7 \sim \phi 23.0$	$\phi 20$	50	100
S20C-MBU23T-60	$\phi 23$	MBU23T	$\phi 22.7 \sim \phi 26.0$	$\phi 20$	60	110
S25C-MBU26-65	$\phi 26$	MBU26	$\phi 25.7 \sim \phi 30.0$	$\phi 25$	65	120
S25C-MBU26T-65		MBU26T				
S25C-MBU30-75	$\phi 30$	MBU30	$\phi 29.7 \sim \phi 36.0$	$\phi 25$	75	130
S25C-MBU30T-75		MBU30T				
S32C-MBU36-80	$\phi 36$	MBU36	$\phi 35.7 \sim \phi 42.0$	$\phi 32$	80	140
S32C-MBU36T-80		MBU36T				
S32C-MBU42-86	$\phi 42$	MBU42	$\phi 41.7 \sim \phi 50.0$	$\phi 32$	86	146
S32C-MBU50-90	$\phi 50$	MBU50	$\phi 49.7 \sim \phi 58.0$	$\phi 32$	90	150
S32C-MBU58-100	$\phi 58$	MBU58	$\phi 57.7 \sim \phi 70.0$	$\phi 32$	100	160
S32C-MBU70-100	$\phi 70$	MBU70	$\phi 69.7 \sim \phi 82.0$	$\phi 32$	100	160

RPATS (for micro-adjustable fine boring tool)

微調單元 MICRO-ADJUSTING UNIT	刀片 INSERTS	刀片座 INSERT SEAT	刀片螺絲 INSERT SCREW	固定螺絲 LOCKING SCREW	刀片板手 INSERT WRENCH	調整板手 ADJUSTING WRENCH	固定板手 LOCKING WRENCH	
								
MBU18	CCGT03S102	M-A-CC03	IS163727	LA0304	T 6	2.5	1.5	
MBU20							2	
MBU23T	TBGT060104	M-A1-TB06	IS200527	LA0406			T 6	2.5
MBU26	EPGT040202	M-A-EP04	IS200527	LA0408	2.5	2		
MBU26T	TBGT060104	M-A2-TB06						
MBU30	EPGT040202	M-A-EP04						
MBU30T	TBGT060104	M-A2-TB06						
MBU36	EPGT040202	M-A-EP04		LA0508	3	2.5		
MBU36T	TBGT060104	M-A2-TB06						
MBU42	CCGT060204	M-A-CC06	IS250638	LA0510	T 8	3		
MBU50								
MBU58	TPGH110304	M-A-TP11	IS300845	LA0610	T 9	4	3	
MBU70								

做任何微調尺寸前,請先將固定螺絲旋鬆,
待調整至所需之尺寸,再將固定螺絲旋緊,
並再次確認尺寸即可。